

Sealants and Lubricants

Glyptol 1201	General Electric Co.	Pipe thread compound and sealant. Bake at 125°F for 2 hours.
Plastic Lead Seal	Crane Packing Co.	Sealing threads and gaskets. Service range to 550°F.
Loctite with Teflon	Loctite Corp.	Sealing pipe and fittings. Temp range -65 to 400°F. Pressure to 600 psi.
Loctite Thread Locker	Loctite Corp.	Removable and permanent thread sealers to 300°F.
<hr/>		
KOPR-KOTE	Jet Lube, Inc.	Not for use on O₂ or LP gas thread lubricant service to 1500°F. For higher temp use Jet Lube SS-30. For S.S. threads only. Not a sealant.
Silver Goop	Crawford Fitting Co.	Anti-seize compound. For S.S. and high temp alloys. Temp range to 2000°F.
Blue Goop	Crawford Fitting Co.	Thread lube for Ti, S.S., and Al to 400°F.

Sealants and Lubricants

Teflon Tape	P.E. O'Hair & Co.	Spec. MIL-T-T 27730. Dupont seal/lubricant for tapered pipe threads.
Torr Seal		seals pipe threads on safety manifolds, etc., hard seal.
Teflon Tape + Fluorolube, Lube 160	Hooker Chemical Co.	Assembly/disassembly of S.S. pipe threads (prevents galling).
Fluorolube, Lube 160	Hooker Chemical Co.	Used on O₂ systems, seal surfaces. Don't use with Al or Mg.
Fomblin, Y-VAC 3 series	Fomblin (K.J. Lesker Co.)	Perfluorinated for hostile environments, both chemical and physical.
PLS-2	Federal Process Co.	Pipe thread sealant (lead base)
SWAK	Cajon Company	Anaerobic sealer with TFE, pipe thread sealant.
Liquid "O" Ring	Oil Center Research, Inc.	All-purpose sealer and lubricant.

Sealants and Lubricants